



Quality is in our nature



Greases

Eurol Ball Bearing Grease EP 2

Multi-Purpose grease for ball and roller bearings

Description

Eurol Ball Bearing Grease EP 2 has been especially developed for the lubrication of ball and roller bearings of motorcycles, mopeds and bicycles.

Eurol Ball Bearing Grease EP 2 is water-repellent and offers a good resistance against oxidation. Moreover, the product has excellent sealing capabilities and a good mechanical stability.

Eurol Ball Bearing Grease EP 2 is highly adhesive and reduces bearing-wear to a minimum and protects all parts from corrosion.

Specifications

Performance level

DIN 51825: KP2K-30

ISO-L-XCCIB 2

Physical properties

Colour	Yellow-brown	
Density at 20°C	0.94 kg/l	ASTM D 1298
NLGI consistency	2	
Thickener type	Lithium	
Base Oil Type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	260 kg	ASTM D 2596
Operating temperature	-30 - 120 °C	
Dropping point	180 °C	

E901210

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com