



Quality is in our nature

Technical fluids - Brakefluids

Eurol Brake Fluid DOT 5 Silic

Silicone-based brake fluid for old-timers / go-karts / Harley Davidson

Description

Eurol Brake Fluid DOT 5 Silicone is a silicone-based brake fluid. The product has a broad temperature range (-55°C up to +260°C) and ensures optimum performance at low temperatures and a low toxicity.

Eurol Brake Fluid DOT 5 Silicone is not suitable for Citroën cars.

Eurol Brake Fluid DOT 5 Silicone helps to prevent corrosion and provides excellent lubrication to rubber seals and metals. It extends brake system life-cycle and will not affect paints.

Eurol Brake Fluid DOT 5 Silicone can safely be used in hydraulic brake and clutch systems of cars, (racing) motorcycles, Harley Davidson bikes, go-karts, old-timers and in industrial applications.

NB: The old brake fluid has to be drained thoroughly from the system before re-fill.

Eurol Brake Fluid DOT 5 Silicone should never be mixed with other brake fluids.

Specifications

Performance level

FMVSS 116 DOT 5

MIL-PRF-46176B

Physical properties

Colour	Purple	
Density at 20°C	0.95 kg/l	ASTM D 1298
Viscosity, kinematic at 100°C	13.9 cSt	ASTM D 445
Flash point	150 °C	ASTM D 93

E801550

Version 1.1, 08-01-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com