



Quality is in our nature

Technical fluids - Aerosols

Eurol Penetrating Oil Spray 400ML

Universal penetrating oil

Description

Eurol Penetrating Oil Spray is a high quality, effective aid for loosening rusted parts.

Eurol Penetrating Oil Spray has, besides good penetrating properties, a corrosion resistant properties.

Eurol Penetrating Oil Spray contains graphite and molybdenum disulfide (MoS₂) which ensures long lasting lubrication.

Eurol Penetrating Oil Spray can be used at applications suchs as:

- Hinges and locks
- Screw connections
- Gears
- Mountings (screws, bolts and nuts)
- Tools

Eurol Penetrating Oil Spray must be shaken well before use. Spray at approx. 20-25 cm from the object. Apply the desired quantity. The Product has to act for 5 to 10

minutes.

Use Eurol Penetrating Oil Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol Penetrating Oil Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

Propriétés physiques

Couleur	incolore à légèrement jaune
Point d'éclair	-20 °C
	ASTM D 93

E701300

Version 1.1, 18-06-2019

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Pays-Bas, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com