



Quality is in our nature

Motorcycle oils 4T - Mineral

Eurol Harley 20W-60

Huile moteur minérale spécialement développée pour les motos Harley

Description

Eurol Harley Davidson oil has especially been developed for Harley Davidson motorcycles. This oil is formulated with selected base stocks and additives, reducing oil consumption to a minimum.

Eurol Harley Davidson oil has been applied for the lubrication of Harley Davidson motorcycles successfully, for many years.

Eurol Harley Davidson withstands heavy shock loads and offers good protection against corrosion and oxidation, so wear is reduced to a minimum. In short: a robust oil for a perfect lubrication which enables the Harley Davidson to last for years.

Specifications

Performance level

API SF/CF

MIL-L-2104B

MIL-L-46152B

Recommended for use

CCMC G2/D1

Propriétés physiques

Couleur	Brun	
Masse volumique à 20°C	0.874 kg/l	ASTM D 1298
Viscosité, cinématique à 40°C	203.5 cSt	ASTM D 445
Viscosité, cinématique à 100°C	23.9 cSt	ASTM D 445
Indice de viscosité	144	ASTM D 2270
Viscosité, dynamique (CCS)	4739 cP	ASTM D 2602
Point d'éclair	209 °C	ASTM D 93
Point d'écoulement	-30 °C	ASTM D 97

E100380

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Pays-Bas, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com