



Quality is in our nature

Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C G11

Long-Life Coolant

Description:

Eurol Coolant -36 G11 is recommended for use in cooling systems of liquid cooled automotive and industrial internal combustion engines.

Eurol Coolant -36 G11 protects car, truck and bus engines of both ferrous and aluminium construction against corrosion and frost damage. It contains a blend of inhibitors designed to give a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads and water pumps. Eurol Coolant -36 G11 provides year-round frost and corrosion protection.

Dilution of the coolant with water is not recommended.

Free of nitrite, amine and phosphate.

Specifications

<u>Performance level</u>	BMW GS 94000 / N 600
VW TL-774 C (G11)	69.0
BS 6580	<u>Recommended for use</u>
ASTM D3306 / D4656 /	SAE J1034
D4985	NATO S-759
AFNOR NFR 15-601	JASO M325
MB 326.2	
MB 326.0	
MAN 324 Typ NF	
MTU MTL 5048	
Fiat 9.55523	

Physical properties

Colour	Green	
Density at 20°C	1.075 kg/l	ASTM D 1298
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177

E504010

Version 1.2, 28-12-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com