





**Greases - Aerosols** 

## **Eurol White Grease PTFE 400ML**

## White lithium grease with PTFE

## **Description**

Eurol White Grease PTFE Spray contains a high quality lubricant based on white lithiumthickener and a PTFE additive suitable for heavy and low speed applications.

Eurol White grease PTFE Spray is perfect for rotating and moving parts made out of metal or plastic. Eurol White grease PTFE Spray has the properties of both an oil and a grease, namely it atomizes as an oil and solidifies as a grease and thus it has good penetrating characteristics as well a good adhesiveness and pressure resistance. Besides these properties, Eurol® White Grease PTFE Spray has excellent water resistance properties and protects against corrosion.

Eurol White Grease PTFE Spray can be used on vertical surfaces, does not drip and run off. Can be used for machines, rollerbearings, axes, gears, conveyor belts and rubber sealing profiles.

The to be treated object must be properly clean, degreased and dry before applying on cold parts.

Eurol White Grease Spray must be shaked well before use. Spray at approx. 20 cm from the object. Apply the desired quantity.

Use Eurol White Grease Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol White Grease Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

## **Physical properties**

Flash point -20 °C ASTM D 93

E701420 Version 1.1, 18-06-2019