

Quality is in our nature



Technical fluids - Chain

Eurol HD Lube for Primar.Chain

Oil for Harley Davidson primary chaincase and diaphragm clutch

Description

Eurol HD Lube for Primary Chaincase has especially been formulated for the lubrication and protection of the primary chain case and the oil bath clutches. Even at extremely low temperatures, an optimal lubrication and a smooth cold start is guaranteed. Because of the special selected additives, rust, corrosion and deposits are reduced to a minimum and water will be repelled.

Eurol HD Lube for Primary Chaincase maintains an extremely consistent lubricating film, even at high temperatures and high speeds. Therefore, offers an optimum protection.

Eurol HD Lube for Primary Chaincase is very suitable for the lubrication of the Primary Chaincase of Harley Davidson models FL, FLT, FXR and FX with oil-batch clutch, from 1984.

It is also suitable for application in ATV's and Snowmobiles, for which such kind of oil is prescribed.

Specifications

Performance level API SF Recommended for use MIL-L-2104D MIL-L-46152C

Physical properties

Colour	Brown	
Density at 20°C	0.855 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	93.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	13.9 cSt	ASTM D 445
Viscosity Index	152	ASTM D 2270
Viscosity, dynamic (CCS)	5654 cP	ASTM D 2602
Base number	4.4 mg KOH/g	ASTM D 2896
Sulphated ash	0.62 wt%	ASTM D 874
Flash point	218 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

E110027 Version 3.3, 16-09-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.