



Quality is in our nature

Scooter oils 2T - Semi-synthetic

Eurol TTX ProScout

Semi-synthetic 2-stroke oil for small air and water cooled 2-stroke engines

Description:

Eurol TTX ProScout is a top quality semi-synthetic 2-stroke oil for the lubrication of air and water cooled 2-stroke engines (up to 50 cc) of mopeds and scooters, with or without an injection system.

"Mixing ratio:

1:50 (if not otherwise prescribed)
"

Eurol TTX ProScout has been tested extensively and is formulated with carefully selected base oils and special additives. It provides an optimum lubrication, also at high temperatures and heavy duty operating conditions.

Eurol TTX ProScout can easily be mixed with petrol (lead free or super) to a homogeneous "pre-mix". It prevents deposits on spark plugs, pistons, inlet and exhaust ports, sticking piston rings and pre-ignition.

Eurol TTX ProScout prevents from wear and corrosion of all vital engine parts and it reduces exhaust outlet smoke. Due to the low sulphated ash contents, the risk of a burned out piston because of pre-ignition or detonation, is very low.

Specifications

Performance level

API TC
JASO FD
ISO-L-EGD
TISI

Physical properties

Colour	Green	
Density at 20°C	0.864 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	64.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.4 cSt	ASTM D 445
Viscosity Index	124	ASTM D 2270
Flash point	92 °C	ASTM D 93
Pour point	-18 °C	ASTM D 97

E128428

Version 3.0, 18-01-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com