

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 9-2-2014 Revision date: 22-8-2019 Supersedes: 27-3-2018 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: Mixture
: Eurol Harley 20W-50
: E100390
: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

- : Industrial use, professional use, Consumer use
- : Lubricant
 - : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol bv. Energiestraat 12 P.O. Box P.O. Box 135 7442 DA Nijverdal - The Netherlands T +31 548 615165 reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number

: +31 79 3467 808 EVOFENEDEX

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 12	72/2008 [CLP]
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs,
	calcium salts, Benzenesulfonic acid, methyl-mono-20-26-branched alkylderivates, calcium
	salt. May produce an allergic reaction.
	EUH210 - Safety data sheet available on request.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards	
Other hazards not contributing to the classification	: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	≥ 50	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit	REACH-no: 01-2119471299- 27, 01-2119484627-25, 01- 2119487077-29	10 – 25	Not classified
Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salt	CAS-No.: 722503-69-7	0,1 – 1	Skin Sens. 1B, H317
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6	0,1 – 1	Skin Sens. 1B, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest.
First-aid measures after skin contact	 Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	 Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.	
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.	
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.	
Symptoms/effects after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.	
Symptoms/effects upon intravenous administration	: Unknown.	

4.3. Indication of an	y immediate medical	attention and	special treatment needed
-----------------------	---------------------	---------------	--------------------------

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	 carbon dioxide (CO2), dry chemical powder, foam. Water fog. Do not use a heavy water stream. Use of heavy stream of water may spread fire. 	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	 Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metal oxides. Not expected to be a fire/explosion hazard under normal conditions of use. 	
5.3. Advice for firefighters		
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	 Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use self-contained breathing apparatus and chemically protective clothing. Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. 	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective	e equipment and emergency procedures	
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.	
6.1.1. For non-emergency personnel		
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.	
Emergency procedures	: Consider evacuation.	
6.1.2. For emergency responders		
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.	
Emergency procedures	: No specific measures are necessary.	
6.2. Environmental precautions		

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up		
For containment	: Large quantities: Contain large spillage with sand or earth.	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,
	sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked
	container for disposal in accordance with local regulations. On water, recover/skim from
	surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	 Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, including any incompatibilities	

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Keep only in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	≤ 40 °C
Information on mixed storage	: Keep away from : oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Highly refined mineral oil (C15 -C50)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOELV TWA (mg/m ³) 5 mg/m ³		
8.1.2. Recommended monitoring procedures		
No additional information available		
8.1.3. Air contaminants formed		

No additional information available

8.1.4. DNEL and PNEC

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed. **Personal protective equipment symbol(s):**



8.2.2.1. Eye and face protection

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

8.2.2.2. Skin protection

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Other skin protection

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

8.2.2.3. Respiratory protection

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and c	hemical properties	
Physical state	: liquid	
Appearance	: Oily. liquid.	
Colour	: brown.	
Odour	: characteristic.	
Odour threshold	: No data available	
pН	: No data available	
Relative evaporation rate (butylacetate=1)	: < 0,1	
Melting point	< -33 ℃	
Freezing point	: No data available	
Boiling point	: > 280 °C	
Flash point	: 205 °C	
Auto-ignition temperature	: > 240 °C	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapour Pressure 20°C	: < 0,1 hPa	
Relative vapour density at 20 °C	: > 1 (air=1)	
Relative density	: No data available	
Density	: 0,87 – 0,88 kg/l	
Solubility	: insoluble in water.	
Log Pow	: >3	
Viscosity, kinematic	: 125 – 160 mm²/s	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidising properties	: No data available	
Explosive limits	: 0,6 – 7 vol %	
9.2. Other information		
VOC content	: 0%	
Other properties	: Gas/vapour heavier than air at 20'C.	

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (dermal)	: Not classified : Not classified : Not classified	
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 5000 mg/kg	
LC50 Inhalation - Rat	> 5,53 mg/l	
Skin corrosion/irritation	Not classified	

Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Eurol Harley 20W-50	
Viscosity, kinematic	125 – 160 mm²/s
Other information	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products,Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Ecology - water Hazardous to the aquatic environment, short-term (acute)	This product floats on water and may affect the oxygen-balance in the water.Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l	
EC50 Daphnia 1	10000 mg/l	
Highly refined mineral oil (C15 -C50)		
EC50 other aquatic organisms 1	≈ 1,2 mg/l	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability			
Eurol Harley 20W-50			
Persistence and degradability	Not readily biodegradable.		
Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salt (722503-69-7)			
Persistence and degradability Not readily biodegradable.			
12.3. Bioaccumulative potential			
Eurol Harley 20W-50			
Log Pow	> 3		
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.		
Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salt (722503-69-7)			
Log Pow	> 3		
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.		
12.4. Mobility in soil			
Eurol Harley 20W-50			
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water		

	contamination. This product floats on water and may affect the oxygen-balance in the water.	
Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salt (722503-69-7)		
Ecology - soil Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.		

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal consideration	\$
13.1. Waste treatment methods	
Regional legislation (waste) Waste disposal recommendations	 Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information Ecology - waste materials	 Hazardous waste. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transpo	rt information			
n accordance with ADR / IMI	DG / IATA / ADN / RID			
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	g name			<u>.</u>
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard o	class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	n available	1		1

14.6. Special precautions for user

Overland transport No data available

Transport by sea No data available

Air transport No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals. Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants VOC content : 0 %

15.1.2. National regulations

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Benzenesulfonic acid, methyl-mono-20-26-branched alkylderivates, calcium salt

SECTION 16: Other information

Full text of H- and EUH-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid, methyl-mono-20-26-branched alkylderivates, calcium salt. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.