



Quality is in our nature

Transmission oils - Mineral

Eurol Universal Gear Oil

Gearbox oils for most occurring mopeds

Description

Eurol Gearbox Oil is a series of special oils for perfect lubrication of the most occurring mopeds.

Eurol Gearbox oils ensure uncomplicated shifting of straight or bevel geared transmissions.

Eurol Gearbox oils have a high viscosity index, ensuring an optimum protection under both low and high temperature conditions.

Specifications

Performance level	Denison Filterability TP
DIN 51524/2 (HLP)	02100
U.S. Steel 127	Bosch Rexroth RE 90220
U.S. Steel 126	CETOP RP 91 H (HM)
VDMA 24318	AFNOR NF E 48-603 (HM)
Thyssen TH N-25613 2	AFNOR NF E 48-603 (HL)
SS 155434	DIN 51524/1 (HL)
Sperry Vickers I-286-S	
Sperry Vickers M-2950-S	
SEB 181 222	
Hoesch HWN 2333	

Physical properties

Colour	Amber	
Density at 20°C	0.884 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	103.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.3 cSt	ASTM D 445
Viscosity Index	95	ASTM D 2270
Flash point	222 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

E126105
Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com