



Quality is in our nature

Motorcycle oils 4T - Fully Synthetic

Eurol Sportbike 10W-60

Fully synthetic motor oil for 4-stroke motorcycles

Description:

Eurol Sportbike 10W-60 Full Synthetic is a fully synthetic engine oil and contains a dedicated ester technology to provide extra protection against wear, deposits, sludge and oxidation under all conditions.

This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ or SL oil is prescribed.

Eurol Sportbike 10W-60 Full Synthetic is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol Sportbike 10W-60 Full Synthetic offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised. Eurol Sportbike 10W-60 Full Synthetic has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

At low temperatures Eurol Sportbike Full Synthetic 5W-40 and 10W-60 rapidly provide a solid lubricant film for an optimum protection of the engine at cold starts.

Specifications

Approved

JASO MA2

Performance level

API SN

JASO MA

Physical properties

Colour	brown	
Density at 20°C	0.857 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	171 cSt	ASTM D 445
Viscosity, kinematic at 100°C	24.6 cSt	ASTM D 445
Viscosity Index	175	ASTM D 2270
Viscosity, dynamic (CCS)	5650 cP	ASTM D 2602
Flash point	206 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

E100082

Version 3.0, 11-03-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com